

## **Silkolene**<sup>®</sup>

### **SILKOLENE PRO CHAIN**

Fully synthetic racing chain lubricant

#### **Description**

A clear, clean, thin film, synthetic chain lubricant designed for maximum fling off resistance when used for racing. Silkolene Pro Chain incorporates a micronized laminar solid lubricant which combined with advanced synthetics gives outstanding boundary lubrication leading to lower friction and reduced wear. Suitable for all chains including “O”, “X” and Z ring types.

#### **Application**

- Ensure chain is clean and dry prior to applying SILKOLENE PRO CHAIN Lube
- We recommend the use of SILKOLENE BRAKE AND CHAIN CLEANER prior to use
- Shake can well before application
- Apply sparingly to the whole length of the inside of a clean warm chain
- Leave for 10 minutes before use
- Wipe away excess

- Following application, invert the can and spray for a few seconds to avoid clogging the nozzle

#### **Advantages / Benefits**

- Good antiwear and shock loading protection even with thin film, low friction, lubrication
- Good resistance to high speed fling off
- Resistant to water wash off
- Penetrates and evaporates quickly with excellent film forming properties
- Thin film formation resists dirt adhesion
- Works at high temperature / high load race conditions
- Good corrosion protection

Updated Nov 2019 ABUK



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products